



HUNTER HVLS FANS

HUNTER MODEL NUMBER	FAN DIAMETER (FT)	Input Power	RATED CURRENT (A)	RPM	COVERAGE (SQFT)	MIN DIST B/W FAN CENTERLINES (FT)	Adjustable DOWNROD SIZE (FT)	WEIGHT (LBS)	Applicable Notes
ECO8	8	AC 1PH 200-240V 50-60HZ	6.5	156	1,600	32	2.5 to 10	87	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	2.0						
ECO10	10	AC 1PH 200-240V 50-60HZ	6.5	139	2,500	40	2.5 to 10	97	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
ECO12	12	AC 1PH 200-240V 50-60HZ	6.5	108	3,600	48	2.5 to 10	101	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
ECO14	14	AC 1PH 200-240V 50-60HZ	6.5	108	4,900	56	2.5 to 10	128	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
ECO16	16	AC 1PH 200-240V 50-60HZ	6.5	94	6,400	64	2.5 to 10	135	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
ECO18	18	AC 1PH 200-240V 50-60HZ	6.5	80	8,100	72	2.5 to 10	138	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
ECO20	20	AC 1PH 200-240V 50-60HZ	6.5	77	10,000	80	2.5 to 10	145	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
ECO24	24	AC 1PH 200-240V 50-60HZ	6.5	62	14,400	96	2.5 to 10	159	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
TITAN14	14	AC 1PH 200-240V 50-60HZ	6.5	103	7,744	70	2.5 to 10	168	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
TITAN16	16	AC 1PH 200-240V 50-60HZ	6.5	95	10,000	80	2.5 to 10	175	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
TITAN18	18	AC 1PH 200-240V 50-60HZ	7.6	93	12,769	90	2.5 to 10	183	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
TITAN20	20	AC 1PH 200-240V 50-60HZ	6.5	73	15,625	100	2.5 to 10	190	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
TITAN24	24	AC 1PH 200-240V 50-60HZ	6.5	64	22,500	120	2.5 to 10	204	1,2,3,4,5,6
		AC 3PH 200-240V 50-60HZ	3.5						
		AC 3PH 380-480V 50-60HZ	3.0						
XP8	8	AC 1PH 100-120V 50-60HZ	8.3	104	1,600	32	2 to 4	104	1,2,4,5,6
XP10	10	AC 1PH 100-120V 50-60HZ	8.3	93	2,500	40	2 to 4	108	1,2,4,5,6
XP12	12	AC 1PH 100-120V 50-60HZ	8.3	71	3,600	48	2 to 4	117	1,2,4,5,6
XP14	14	AC 1PH 100-120V 50-60HZ	8.3	72	4,900	56	2 to 4	121	1,2,4,5,6

Schedule Notes

1. Permanent Magnet Direct Drive Motor
2. Digital Touchscreen with the ability to network up to 30 fans
3. Telescoping Downrod - Adjustable every 6"
4. BMS Integration
5. VFD to be located outside the swept area of the blades
6. Compliant with NFPA 13 & 72 regulations

w.w.Cannon, Inc.
Design. Layout. Build. Install.
 1-800-442-3061
 www.wwcannon.com