

Storage Units



FEATURES

- Secures equipment & valuables
- Allows light, ventilation & fire suppression systems to work effectively.
- Easy to setup & reconfigure for maximum flexibility
- Use individually or configure in multiples for larger spaces

SPECIFICATIONS

- **Mesh:** 1.5" diamond 16-gauge standard expanded metal
- **Frame:** MIG-welded & pre-punched for installation
- **Side Panel:** 1.25" x 1.25" 14-gauge formed angles
- **Doors:** 1.5" x 1" 14-gauge formed channel outer frames & 1.5" x 1" 12-gauge formed angle inner frames
- **Finish:** Gray powder coat
- **Warranty:** 1 year



Product Code	Depth	Width	Height	Weight (lbs)
TSL-ST133	36"	36"	90"	170
TSL-AD133	36"	36"	90"	115
TSL-ST233	36"	36"	90"	205
TSL-AD233	36"	36"	90"	135
Ceiling 36"	36"	36"	90"	25
Back 36"	36"	36"	90"	60
TSL-ST144	48"	48"	90"	225
TSL-AD144	48"	48"	90"	150
TSL-ST244	48"	48"	90"	270
TSL-AD244	48"	48"	90"	180
Ceiling 48"	48"	48"	90"	40
Back 48"	48"	48"	90"	75

Custom configurations, sizes & colors available.

ACCESSORIES

- **1 Padlock:** 2" hardened steel with plated shackle (sold separately)

