

# TILT N ROLL LADDERS<sup>®</sup>



- 4 STANDING HEIGHTS
- ALUMINUM
- 304 STAINLESS STEEL
- POWDER COATED STEEL



## Cotterman Co.

Division of Material Control, Inc.

**w.w.Cannon, Inc.**

Design. Layout. Build. Install.

1-800-442-3061  
www.wwcannon.com



The TILT NROLL® features a special balanced design that allows it to tilt easily to the rolling position when pulled toward the user. The user is not required to extend a foot to assist in tilting the ladder to the rolling position. Once tilted, the ladder can be easily moved from job to job on the two 4" diameter wheels.

TILT NROLL® ladders are one-piece welded assemblies shipped ready to use. The ladders are supplied with handrails that extend 30" above the top step. They are designed to meet OSHA 1910 Subpart D, and ANSI A14.7 standards. Cal-OSHA models are also available. 59° climb angle.

## SPECIFICATIONS AND PRICING

CHOOSE FROM EXPANDED METAL, PERFORMA OR GRIP STRUT STEPS	NUMBER OF STEPS	TOP STEP HEIGHT	SINGLE TOP STEP				DOUBLE TOP STEP				
			16"Wx10"D		24"Wx10"D		16"Wx20"D		24"Wx20"D		
			MODEL	BASE W"xL"	SHPG. WT.	PRICE	MODEL	BASE W"xL"	SHPG. WT.	PRICE	MODEL

**POWDER COATED STEEL:** (450 LB. LOAD RATING) STANDARD COLOR: GRAY (AVAILABLE) SAFETY YL., ORANGE, DK. BROWN & BLACK.

	2	20"	2TR18	20x24	38		2TR26	28x24	43		2TR18E4	20x34	49		2TR26E4	28x34	60	
	3	30"	3TR18	20x30	47		3TR26	28x30	55		3TR18E4	20x41	62		3TR26E4	28x41	71	
	4	40"	4TR18	20x37	58		4TR26	28x37	66		4TR18E4	20x47	72		4TR26E4	28x47	83	
	5	50"	5TR18	20x43	68		5TR26	28x43	78		5TR18E4	20x54	82		5TR26E4	28x54	95	
	2	20"	2TR18A6	20x24	36		2TR26A6	28x24	40		2TR18E4A6	20x34	46		2TR26E4A6	28x34	59	
	3	30"	3TR18A6	20x30	45		3TR26A6	28x30	51		3TR18E4A6	20x41	60		3TR26E4A6	28x41	69	
	4	40"	4TR18A6	20x37	54		4TR26A6	28x37	62		4TR18E4A6	20x47	70		4TR26E4A6	28x47	79	
	5	50"	5TR18A6	20x43	64		5TR26A6	28x43	73		5TR18E4A6	20x54	79		5TR26E4A6	28x54	90	
	2	20"	2TR18A3	20x24	36		2TR26A3	28x24	40		2TR18A3E4	20x34	49		2TR26A3E4	28x34	56	
	3	30"	3TR18A3	20x30	45		3TR26A3	28x30	51		3TR18A3E4	20x41	59		3TR26A3E4	28x41	67	
	4	40"	4TR18A3	20x37	55		4TR26A3	28x37	62		4TR18A3E4	20x47	68		4TR26A3E4	28x47	78	
	5	50"	5TR18A3	20x43	64		5TR26A3	28x43	73		5TR18A3E4	20x54	78		5TR26A3E4	28x54	88	

**#304 STAINLESS STEEL:** (450 LB. LOAD RATING) SAND BLASTED SATIN FINISH

	2	20"	2TS18	20x24	54		2TS26	28x24	59		2TS18E4	20x34	68		2TS26E4	28x34	75	
	3	30"	3TS18	20x30	71		3TS26	28x30	77		3TS18E4	20x41	86		3TS26E4	28x41	95	
	4	40"	4TS18	20x37	88		4TS26	28x37	97		4TS18E4	20x47	103		4TS26E4	28x47	113	
	5	50"	5TS18	20x43	106		5TS26	28x43	116		5TS18E4	20x54	117		5TS26E4	28x54	133	
	2	20"	2TS18A3	20x24	53		2TS26A3	28x24	57		2TS18A3E4	20x34	63		2TS26A3E4	28x34	73	
	3	30"	3TS18A3	20x30	70		3TS26A3	28x30	76		3TS18A3E4	20x41	83		3TS26A3E4	28x41	91	
	4	40"	4TS18A3	20x37	86		4TS26A3	28x37	93		4TS18A3E4	20x47	100		4TS26A3E4	28x47	109	
	5	50"	5TS18A3	20x43	104		5TS26A3	28x43	112		5TS18A3E4	20x54	118		5TS26A3E4	28x54	127	

**ALUMINUM:** (350 LB. LOAD RATING) 6061-T6 HIGH STRENGTH ALLOY

	2	20"	2TA18A3	20x24	17		2TA26A3	28x24	19		2TA18A3E4	20x34	21		2TA26A3E4	28x34	24	
	3	30"	3TA18A3	20x30	23		3TA26A3	28x30	24		3TA18A3E4	20x41	26		3TA26A3E4	28x41	30	
	4	40"	4TA18A3	20x37	26		4TA26A3	28x37	29		4TA18A3E4	20x47	30		4TA26A3E4	28x47	35	
	5	50"	5TA18A3	20x43	30		5TA26A3	28x43	34		5TA18A3E4	20x54	35		5TA26A3E4	28x54	40	

# w.w.Cannon, Inc.

Design. Layout. Build. Install.

1-800-442-3061  
www.wwcannon.com



MEMBER  
SIA  
SPECIALTY INDUSTRIES ASSOCIATION

MEMBER  
MHIA  
MANUFACTURERS HANDBOOK OF INDUSTRIAL ACCESSORIES



National  
Safety  
Council

MEMBER  
ANSI

WARRANTY

All Cotterman products are guaranteed against defects in workmanship and materials for a period of one (1) year after shipment.

F.O.B. FACTORY • TERMS: NET 30 DAYS

TAX NOT INCLUDED • PRICES SUBJECT TO CHANGE WITHOUT NOTICE