

LadderGuard™

Fall Prevention for Fixed Ladders

Meets OSHA Requirements

1910.29(b) and 1926.502(b)

Features:

- An OSHA compliant fall prevention solution for fixed ladders
- Modular components makes it easy to bring through a hatch
- Non-penetrating design maintains the watertight integrity of the roof
- Adjustable ladder connectors closes off the gap between the fixed ladders and LadderGuard rails
- Accommodates both round and square fixed ladder handrails



OSHA Compliant

Garlock Safety Systems LadderGuard keeps people away from the fall edge by creating an OSHA approved barriers to the left and right of the leading edge. It prevents people from taking a sharp turn at the top of the ladder and coming with 6' of the fall edge. Garlock's LadderGuard is third party certified to be OSHA compliant.

Modular Design

Its modular design breaks down into manageable pieces to reduce carrying weight and allows it to be brought up to the roof through standard sized hatches. The adjustable ladder connectors provide a wide range of application flexibility.

Putting Safety at the Top

For the utmost in safety, select from either the yellow or galvanized version with a color matched EasyFit™ self-closing gate. As soon as someone walks down the protective corridor they will step onto the roof and the gate will automatically close behind them protecting the worker and keeping them safe.

Why Choose Garlock?

- Rigorously Tested to Exceed OSHA & ANSI Standards
- In-House Engineering
- 100+ Years of Industry Experience
- Full Passive Fall Prevention Portfolio
- Custom Engineered Products Available

Features



Non-penetrating weighted base maintains a watertight roof.



Ladder connectors close off the gap between the fixed ladder and the LadderGuard.



Models equipped with EasyFit gate provided an extra level of safety.



5' rails with ladder connectors ensure workers are at least 6' onto the roof before they exit.



Auxiliary ports for connecting warning lines or guardrail system.



Accommodates square or round fixed ladder components.

Specifications

Top rail height	42"
Midrail height	21"
Rails	16-gauge steel, 5' long, yellow or galvanized
Base	3/8" thick, six ports, galvanized
Ladder connectors	Steel, adjustable between 24" and 34"
EasyFit gate	Powder coated plate or galvanized

Due to continuous improvement, specifications are subject to change without notice.

LadderGuard Kits

449-001-001	6' system complete, without gate, safety yellow
449-001-600	6' system complete, without gate, galvanized
449-002-001	6' system complete, with EasyFit gate, safety yellow
449-002-600	6' system complete, with EasyFit gate, galvanized
449-003-600	6' system complete, modular Fit-Rite components, galvanized
449-004-600	6' system complete, modular Fit-Rite components, with gate, galvanized