

Permanent Mount Railings

Meets OSHA Requirements

1926.502(b)(3) and (b)(4), 1910.29(b)(3) and (b)(4)

Permanent guardrail system solutions can be used in many locations, both inside and outside your facility. Permanent guardrail systems can be used for loading docks, stairways, mezzanines or machinery hazard areas. With one of our many base options, we can customize a solution to meet your needs. Available in a variety of colors to match your facility or order them in standard safety yellow.

Features

- 16 gauge construction welded rail sections that secure to floor or wall areas for permanent applications.
- Standard lengths from 2 to 12 feet. *Custom lengths also available.*
- Safety yellow standard powder coat. Many color options available.
- Multiple base mounting option.



Why Choose Garlock Safety Systems™?

- Rigorously Tested to Exceed OSHA & ANSI Standards
- In-House Engineering
- Full Passive Fall Prevention Portfolio
- Custom Engineered Products Available

Features



Single Post Floor Mount



Double Post Floor Mount



Box Floor Mount



Zip Base



Wrap Over Box Mount



Wrap Over Double Post



Flush Mount Single Post



Flush Mount Double Post

Specifications

	Weight (lbs)	Floor Space (in)		Wall Space (in)	
		Width	Length	Width	Height
Single Post Floor Mount	5	5.5	7.5	NA	NA
Double Post Mount	6	5.5	7.5	NA	NA
Box Floor Mount	9	6.5	7.5	NA	NA
Zip Base	2.3	3.25	5.5	NA	NA
Wrap Over Single Post	8	8	6	8	8.75
Wrap Over Double Post	10	9	6	9	8.75
Flush Mount Single Post	8	NA	NA	8	8.75
Flush Double Post	10	NA	NA	10	8.75
Wrap Over Box Mount	10	9	6	9	8.75

- Railing Lengths: 5', 7.5', 10'
- Railing Diameter: 1-5/8"
- Weight: 23-28 lbs

