



# Flex LED Dock Light

## Lighting & Communication



### FEATURES

- Energy efficient - operates on 10W
- Uses 84% less energy than 150W models
- Provides light comparable to an incandescent 150W PAR38 lamp
- Long-life LEDs (rated 50,000 hours) deliver bright, uniform, instant-on light
- Easy installation mounting bracket compatible with most dock light mounting hardware
- Flexible arm offers great flexibility in positioning
- High-temperature polymer housing resists denting and wear
- Vented housing help maintain LED longevity
- With no filament to break, solid state lighting proves far more durable than incandescent sources
- Polycarbonate available for food applications at not extra charge
- Design and manufactured in the USA

# Phoenix Flex LED Docklite®

## Lighting & Communication



### SPECIFICATIONS

|                               |   |
|-------------------------------|---|
| Construction                  | Thermally conductive plastic housing  |
| Hardware                      | 304 stainless steel   |
| Arm                           | Flexible tubing   |
| Lens                          | Impact resistant<br>Clear polycarbonate   |
| Light Source                  | Lumileds Luxeon light emitting diodes (LED) 10W, up to 1100 lumens<br>CRI > 70<br>CCT 4000K<br>20' beam pattern<br>50,000 hour rated life       |
| Power Source                  | 100-277V (pigtail) or 120V only (with NEMA 5-15 plug)<br>Bi-level dimming standard  |
| Wiring                        | 72.00 inch (1829 mm) cord with three-prong plug (NEMA 5-15) (standard on 120V only)<br>72.00 inch (1829 mm) cord with pigtail (100-277V option) |
| Ambient operating temperature | -40°C to +40°C  |
| Mounting                      | 3x5 inch zinc plated steel bracket  |
| Weight                        | 7.0 lb (3.2 kg)   |
| Warranty                      | 3 years   |



### DIMENSIONS

