YellowGate Protection, only BIGGER Part No. 108490-XL

Powder coated

safety yellow

YellowGate W



Each component is proudly crafted in ou South Carolina facilit

On-site adjustable tension spring.

Three points of adjustment for optimized balance, light touch, smooth operation and easy action movement.

52"

[1321 mm]

SillowGate WX

11"

[279 mm]

90° movement

Easy action

movement

26"

[660 mm]

Ultra lightweight.

Lifts and lowers almost

The Most Adjustable

Barrier Gate Available.

OSHA Compliant

Part No. 108490-XL

Durable weather protection design

42" [1067 mm]

wers almost effortlessly.

PRODUCT KEY FEATURES:

- Adjustable from 6' [1829 mm] -12' [3658 mm],
 42" [1067 mm] height
- Powder coated safety yellow
- Aluminum extruded, laser precision manufactured
- Lightweight and easy to raise and lower
- Maintenance free ergonomic design
- Locking pin for both the open and closed positions

Available Power Option

Available with an optional 24 volt powered lift assist system, requiring a 120 volt power supply.

- Standard 50 ft. (customer to cut to desired length) cable run from controller to gate. (max. 150 ft.)
- Retro-fitable to existing manual YGXL rev3 models.
- Easy installation with basic tools
- Some electrical connection by customer required
- 15-20 second, 90 degree raise or lower

