

Narrow Applications



Model B - Twin Pad Load Beam - Standard Duty

For lifting smaller rectangular shaped material. Width should not exceed 5 times the pad diameter (see specifications below for pad diameter).

QUICKSHIP PROGRAM

PRODUCT FEATURES:

- Ball mounted vacuum pads.
- Brass fittings.
- Push lock hose (designed for 250 psi).
- Slide valves allow for manual isolation of vacuum pads.
- Muffler/filter is spin on type for easy change out.



SPECIFICATIONS

Add FEET to blank Model Number box to complete code.
Example: 4' load beam BE1S4- **LENGTH**

Rated Capacity (lbs.)	Base Wt. @ 4' (lbs.)	Model Number	Power-Pac	Flared Diameter (in.)	Load Beam Length (ft.)			
					4	5	6	8
Electric								
160	130	BE1S4 <input type="text"/>	UNIVAC-250	5	4	5	6	8
340	135	BE3S6 <input type="text"/>	UNIVAC-250	7-1/4	4	5	6	8
620	140	BE6S8 <input type="text"/>	UNIVAC-250	9-5/8	4	5	6	8
800	150	BE8V8 <input type="text"/>	UNIVAC-250	10-5/8	4	5	6	8
1200	230	BE12V10 <input type="text"/>	UNIVAC-250	12-1/4	4	5	6	8
1600	240	BE16V12 <input type="text"/>	UNIVAC-250	14-1/4	4	5	6	8
2000	260	BE20V14 <input type="text"/>	UNIVAC-250	16	4	5	6	8
Shop Air - Venturi								
160	140	BA1S4 <input type="text"/>	V-40	5	4	5	6	8
340	170	BA3S6 <input type="text"/>	V-40	7-1/4	4	5	6	8
620	175	BA6S8 <input type="text"/>	V-40	9-5/8	4	5	6	8
800	180	BA8V8 <input type="text"/>	V-40	10-5/8	4	5	6	8
1200	190	BA12V10 <input type="text"/>	V-40	12-1/4	4	5	6	8
1600	200	BA16V12 <input type="text"/>	V-40	14-1/4	4	5	6	8
2000	210	BA20V14 <input type="text"/>	V-40	16	4	5	6	8

Other sizes available, consult factory.