

# Nominal Surface Area Applications

## Model A - Single Pad - Standard Duty

For lightweight material with small square shaped surface. Neither the width or the length should exceed 5 times the pad diameter (see specifications below for pad diameter).

**QUICKSHIP  
PROGRAM**



### PRODUCT FEATURES:

- Ball mounted vacuum pads.
- Brass fittings.
- Push lock hose (designed for 250 psi).
- Muffler/filter is spin on type for easy change out.

### SPECIFICATIONS

Rated Capacity (lbs.)	Wt. (lbs.)	Model Number	Power-Pac	Flared Diameter (in.)
<b>Electric</b>				
170	78	<b>AE1S6</b>	UNIVAC-250	7-1/4
310	80	<b>AE3S8</b>	UNIVAC-250	9-5/8
400	84	<b>AE4V8</b>	UNIVAC-250	10-5/8
600	87	<b>AE6V10</b>	UNIVAC-250	12-1/4
800	95	<b>AE8V12</b>	UNIVAC-250	14-1/4
1000	108	<b>AE10V14</b>	UNIVAC-250	16
1500	202	<b>AE15V16</b>	UNIVAC-250	19
2000	213	<b>AE20V20</b>	UNIVAC-250	23
<b>Shop Air - Venturi</b>				
170	20	<b>AA1S6</b>	V-40	7-1/4
310	22	<b>AA3S8</b>	V-40	9-5/8
400	28	<b>AA4V8</b>	V-40	10-5/8
600	30	<b>AA6V10</b>	V-40	12-1/4
800	33	<b>AA8V12</b>	V-40	14-1/4
1000	51	<b>AA10V14</b>	V-40	16
1500	53	<b>AA15V16</b>	V-40	19
2000	55	<b>AA20V20</b>	V-40	23

Other sizes available, consult factory.

**w.w.Cannon, Inc.**  
Design. Layout. Build. Install.  
1-800-442-3061  
www.wwcannon.com