

| Model<br>Number | Capacity<br>(tons) | Dimensions (inches) |      |            |          |       |   |   |       |   |       |        |        |
|-----------------|--------------------|---------------------|------|------------|----------|-------|---|---|-------|---|-------|--------|--------|
|                 |                    | Coil I.D.           |      | Coil       | HR       |       |   |   |       |   |       |        | Weight |
|                 |                    | Min.                | Max. | Width<br>W | Headroom | Α     | В | С | Т     | F | D     | J      | (lbs.) |
| 83HW-2-1/2-24   | 2-1/2              | 16                  | 24   | 20         | 36       | 1-1/2 | 3 | 5 | 3/4   | 5 | 3/4   | 15-1/2 | 250    |
| 83HW-5-24       | 5                  | 16                  | 24   | 24         | 41       | 2     | 4 | 7 | 1     | 6 | 1     | 15-1/2 | 350    |
| 83HW-7-1/2-24   | 7-1/2              | 16                  | 24   | 24         | 42       | 2     | 4 | 7 | 1     | 6 | 1     | 15-1/2 | 425    |
| 83HW-10-24      | 10                 | 16                  | 24   | 30         | 50       | 2-1/2 | 5 | 9 | 1-1/4 | 6 | 1-1/2 | 15-1/2 | 500    |

Other sizes available, consult factory.

Get Custom Quotes Quickly

COIL I.D.

**Distributors can get quotes for custom equipment quickly** with Caldwell's Smart Spec configurator tool on the new, online Distributor Portal. Ask for access today at 800.628.4263.



