

VRBS

VIP-Load ring for welding.



PRODUCT FEATURES

- Large WLL range 4 t – 31.5 t.
- Clear indication of the minimum WLL for all loading directions.
- Patented wear markings for easy determination of wear.
- Distance knobs on the weld-on block for the necessary distance for root welding.
- The weld-on block is forged from a material that is easy to weld.



✓ Corresponds with the test criteria of BG/DGUV "GS-OA-15-04".

- Split force introduction thanks to multiple point fixing.
- Suspension ring pivots 180°.
- WLL possible up to 90° in load ring plane.

VRBS / VRL / VASK

Technical data.

VRBS – VIP-LOAD RING FOR WELDING.

| Type | WLL [t] | Weight (kg/unit) | T [mm] | A [mm] | B [mm] | C [mm] | D [mm] | E [mm] | F [mm] | Welding seam | Ref. No. |
|------------|---------|------------------|--------|--------|--------|--------|--------|--------|--------|--------------|----------|
| VRBS 4t | 4 | 0.8 | 65 | 62 | 14 | 28 | 48 | 135 | 71 | HY 4 + a3 | 7992488 |
| VRBS 6.7t | 6.7 | 1.6 | 84 | 88 | 20 | 39 | 60 | 170 | 92 | HY 5.5 + a3 | 7992489 |
| VRBS 10t | 10 | 2.6 | 95 | 100 | 22 | 46 | 65 | 195 | 100 | HY 6 + a4 | 7992490 |
| VRBS 16t | 16 | 5.53 | 127 | 130 | 30 | 57 | 90 | 263 | 134 | HY 8.5 + a4 | 7992491 |
| VRBS 31.5t | 31.5 | 15.6 | 178 | 160 | 42 | 79 | 130 | 375 | 195 | HY 18 + a4 | 60267 |

Subject to technical changes!

VRL-FIX-OCTAGONAL RING LINK (UNIVERSAL DESIGN FOR VRBS-FIX AND VRBS).

| Type | WLL [t] | Weight (kg/unit) | T [mm] | A [mm] | B [mm] | C [mm] | D [mm] | E [mm] | F [mm] | G | Ref. No. |
|---------------|---------|------------------|--------|--------|--------|--------|--------|--------|--------|-----|----------|
| VRL-FIX 4t | 4 | 0.4 | 55 | 107 | 14 | 69 | 48 | 17 | 18 | 76 | 7906890 |
| VRL-FIX 6.7t | 6.7 | 0.93 | 71 | 134 | 19 | 90 | 60 | 23 | 24 | 99 | 7906891 |
| VRL-FIX 10t | 10 | 1.44 | 78 | 152 | 19.5 | 97 | 65 | 28 | 29 | 105 | 7906892 |
| VRL-FIX 16t | 16 | 3.2 | 104 | 204 | 27.5 | 131 | 90 | 35 | 37 | 146 | 7906893 |
| VRL-FIX 31.5t | 31.5 | 8.8 | 152 | 292 | 41 | 193 | 130 | 46 | 47 | 214 | 7906894 |

Subject to technical changes!

VASK – VRBS-WELD-ON BLOCK.

| Type | WLL [t] | Weight (kg/unit) | T [mm] | A [mm] | B [mm] | C [mm] | D [mm] | E [mm] | F [mm] | Welding seam | Ref. No. |
|------------|---------|------------------|--------|--------|--------|--------|--------|--------|--------|--------------|----------|
| VASK 4t | 4 | 0.13 | 19 | 62 | - | 28 | - | - | 30 | HY 4 + a3 | 7992004 |
| VASK 6.7t | 6.7 | 0.34 | 24 | 88 | - | 39 | - | - | 36 | HY 5.5 + a3 | 7992005 |
| VASK 10t | 10 | 0.63 | 31 | 100 | - | 46 | - | - | 46 | HY 6 + a4 | 7992007 |
| VASK 16t | 16 | 1.3 | 39 | 130 | - | 57 | - | - | 57 | HY 8.5 + a4 | 7992008 |
| VASK 31.5t | 31.5 | 3.24 | 49 | 160 | - | 78 | - | - | 82 | HY 18 + a4 | 7987160 |

Subject to technical changes!

