





Model FR

Locking Type

The Model FR is a vertical lifting tool for relatively light work. It is small and easy to handle in capacities through three tons. It incorporates a "Lock Closed" feature which facilitates attaching the clamp to the plate.







Lock assembly is inside the clamp body to keep it out of the way.

MODEL FR SPECIFICATIONS (in inches)

	Part Number	Plate Thickness A		С	Max. D	E	F		н	J	Weight (lbs.)
	1/2 Tons Capacity	,									,
STOCK	FR-00.50-A	0-3/4	2-13/16	7	11-1/4	2-3/8	4-5/8	2-1/2	1-1/2	1/2	8
	FR-00.50-B	1/2 – 1	2-13/16	7	11-1/4	2-3/8	4-7/8	2-1/2	1-1/2	1/2	8
	FR-00.50-C	3/4 – 1-1/4	2-13/16	7	11-1/4	2-3/8	5-1/8	2-1/2	1-1/2	1/2	9
	FR-00.50-D	1 – 1-1/2	2-13/16	7	11-1/4	2-3/8	5-3/8	2-1/2	1-1/2	1/2	10
	FR-00.50-E	1-1/4 - 1-3/4	2-13/16	7	11-1/4	2-3/8	5-3/8	2-1/2	1-1/2	1/2	11
	1 Tons Capacity										
STOCK	FR-01.00-A	0-3/4	3-3/16	9	13-3/4	2-7/16	5-7/8	3-3/16	1-5/8	5/8	14
	FR-01.00-B	1/2 – 1	3-3/16	9	13-3/4	2-7/16	6-1/8	3-3/16	1-5/8	5/8	15
	FR-01.00-C	3/4 – 1-1/4	3-3/16	9	13-3/4	2-7/16	6-3/8	3-3/16	1-5/8	5/8	15
	FR-01.00-D	1 – 1-1/2	3-3/16	9	13-3/4	2-7/16	6-5/8	3-3/16	1-5/8	5/8	16
	FR-01.00-E	1-1/4 - 1-3/4	3-3/16	9	13-3/4	2-7/16	6-7/8	3-3/16	1-5/8	5/8	17
	FR-01.00-F	1-1/2 - 2	3-3/16	9	13-3/4	2-7/16	7-1/8	3-3/16	1-5/8	5/8	18
	2 Tons Capacity										
STOCK	FR-02.00-A	0-1	3-1/2	9	16-3/8	3-5/8	6-3/4	3-3/8	2-1/8	3/4	23
	FR-02.00-B	3/4 – 1-1/2	3-1/2	9	16-3/8	3-5/8	7-1/4	3-3/8	2-1/8	3/4	23
	FR-02.00-C	1-1/4 – 2	3-1/2	9	16-3/8	3-5/8	7-3/4	3-3/8	2-1/8	3/4	23
	FR-02.00-D	1-3/4 - 2-1/2	3-1/2	9	16-3/8	3-5/8	8-1/4	3-3/8	2-1/8	3/4	24
	3 Tons Capacity										
STOCK	FR-03.00-A	0 - 1-1/4	4-3/16	10-3/4	18-3/8	3-5/8	7-5/8	3-9/16	2-7/16	3/4	30
	FR-03.00-B	3/4 – 1-1/2	4-3/16	10-3/4	18-3/8	3-5/8	7-7/8	3-9/16	2-7/16	3/4	31
	FR-03.00-C	1-1/4 – 2	4-3/16	10-3/4	18-3/8	3-5/8	8-3/8	3-9/16	2-7/16	3/4	32
	FR-03.00-D	1-3/4 - 2-1/2	4-3/16	10-3/4	18-3/8	3-5/8	8-7/8	3-9/16	2-7/16	3/4	33

Consult factory for possible larger capacities. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

