



ROLLING SLIDE GATE FOR MEZZANINES

The space-efficient operation of Wildeck's Rolling Slide Gate makes it an ideal gate for mezzanine/deck surfaces. Built into new or existing railing systems, the gate parallels the guard rail plane, occupying a minimal amount of floor space.

Personnel can work with peace-of-mind as they stand safely behind the gate and guard rail for the duration of the sliding motion. Wildeck's Rolling Slide Gate is trackless, leaving the horizontal deck space clear. The gate rides on silent, polyurethane wheels, and securely latches when closed — providing safe access to pallet loads.

Highlights

- Occupies minimal deck footprint
- Custom sizes available
- Designed in compliance with OSHA and CAL/OSHA requirements

STANDARD SPECIFICATIONS

- 1-1/2" Square steel tube construction
- Provides 42" H guard rail protection with toe board
- Required horizontal clearance is twice the length of the gate opening plus 36"
- Two (21" sphere test) or three (12" sphere test) rail options available
- Designation of left or right side opening needed (orientation direction is looking off deck to floor)
- Freestanding surface mounted (standard) and custom mounting options available
- Wildeck yellow paint finish for high visibility (other colors available)



Wildeck® Rolling Slide Gate (SL-GS5)

Model #	Gate Clear Opening Width	Horizontal Clearance Required	Shipping Weight
SL-GS4	4 ft.	132"	107 lbs.
SL-GS5	5 ft.	156"	112 lbs.
SL-GS6	6 ft.	180"	117 lbs.
SL-GS7	7 ft.	204"	122 lbs.
SL-GS8	8 ft.	228"	127 lbs.

EDGEALERT™ COMPATIBLE

Open gates at elevated mezzanine platforms present a serious safety hazard and can result in large fines during an OSHA inspection. Wildeck's EdgeAlertTM Open Gate Alarm signals an open gate condition with flashing LED lights and a highly audible alarm.



